CLAIMS

What is Claimed is:

5

20

A minimum signature solid propellant formulation comprising:
about 6.0 to about 9.0 weight % of at least one polymeric binder;
about 21 to about 25 weight % of at least one energetic plasticizer;
about 25 to about 45 weight % of ammonium dinitramide prills having a
particle size of about 100 μm to about 200 μm as an ADN prills
oxidizer; and

about 15 to about 25 weight % of CL-20.

- 10 2. The solid propellant formulation of Claim 1, wherein said CL-20 has a particle size of about 3 μ m.
 - 3. The solid propellant formulation of Claim 1, wherein said binder is selected from the group consisting of polycaprolactone, poly(diethyleneglycol-4,8-dinitraza undeconate) and polyglycidal nitrate.
- 15 4. The solid propellant formulation of Claim 1, wherein said plasicizer is selected from the group consisting of butanetriol trinitrate, trimethylolethane trinitrate, n-n-butyl-N-(2-nitoxyethyl)nitramine and any combination thereof.
 - 5. The solid propellant formulation of Claims 1, further comprising at least one member selected from a curative, a stabilizer, a cure catalyst, crosslinker, a burn rate modofier and a bonding agent.
 - 6. The solid propellant formulation of Claim 5, wherein said curative is selected from the group consisting of hexamethylene diisocyanate, m-tetramethylxylene diisocyanate, dimeryl diisocyanate, toluene diisocyanate, polymeric

Patent Application Navy Case No. 95946

5

15

hexamethylene diisocyanate, isophorone diisocyanate, biuret triisocyanate and any combination thereof.

- 7. The solid propellant formulation of Claim 5, wherein said cure catalyst is selected from the group consisting of triphenyl bismuth triphenyltin chloride, dibutyltin diacetate and dibutyltin dilaurate.
- 8. The solid propellant formulation of Claim 5, wherein said stabilizer is selected from the group consisting of N-methyl-p-nitroaniline and 2-NDPA (2-nitrodiphenylamine).
- 9. The solid propellant formulation of Claim 5, wherein said burn rate modifier is carbon black.
 - 10. The solid propellant formulation of Claim 5, wherein said crosslinker is nitrocellulose.
 - 11. A minimum signature solid propellant formulation comprising:

about 6.0 to about 9.2 weight % of at least one polymeric binder; about 21 to about 28 weight % of at least one energetic plasticizer; about 35 to about 45 weight % of ammonium dinitramide prills having a particle size of about 100 μm to about 200 μm as an ADN prills oxidizer; and

about 15 to about 25 weight % of CL-20.

- The solid propellant formulation of Claim 11, wherein said polymeric binder is polycaprolactone.
 - 13. The solid propellant formulation of Claim 11, wherein said energetic plasticizer comprises:

Patent Application Navy Case No. 95946

10

20

about 4.0 to about 6.0 weight % of butanetriol trinitrate; about 7.0 to about 9.0 weight % of trimethylolethane trinitrate; and about 10.0 to about 13.0 weight % of n-n-butyl-N-(2-nitoxyethyl)nitramine.

- The solid propellant formulation of Claim 11, further comprising at least one member selected from a curative, a stabilizer, a cure catalyst, crosslinker, a burn rate modifier and a bonding agent.
 - 15. A minimum signature solid propellant formulation comprising:

about 6.0 to about 9.0 weight % of at least one polymeric binder; about 20 to about 34 weight % of at least one energetic plasticizer; about 25 to about 45 weight % of ammonium dinitramide prills having a particle size of about 100 μm to about 200 μm as an ADN prills oxidizer; and

about 15 to about 25 weight % of CL-20.

- 15 16. The solid propellant formulation of Claim 15, wherein said polymeric binder is poly(diethyleneglycol-4,8-dinitraza undeconate).
 - 17. The solid propellant formulation of Claim 15, wherein said energetic plasticizer comprises:

about 5.0 to about 12.0 weight % of butanetriol trinitrate; and about 15.0 to about 22.0 weight % of trimethylolethane trinitrate.

18. The solid propellant formulation of Claim 15, further comprising at least one member selected from a curative, a stabilizer, a cure catalyst, crosslinker, a burn rate modifier and a bonding agent.

Patent Application Navy Case No. 95946

19. A minimum signature solid propellant formulation comprising:

about 6.0 to about 10.5 weight % of at least one polymeric binder; about 12 to about 32 weight % of at least one energetic plasticizer; about 25 to about 45 weight % of ammonium dinitramide prills having a particle size of about 100 μm to about 200 μm as an ADN prills oxidizer; and

about 15 to about 25 weight % of CL-20.

- 20. The solid propellant formulation of Claim 19, wherein said polymeric binder is polyglycidal nitrate.
- The solid propellant formulation of Claim 19, wherein said energetic plasticizer comprises:

about 0 to about 7.0 weight % of said butanetriol trinitrate; about 10.0 to about 15.0 weight % of said trimethylolethane trinitrate; and about 2.0 to about 10.0 weight % of said n-n-butyl-N-(2-nitoxyethyl)nitramine.

22. The solid propellant formulation of Claim 19, further comprising at least one member selected from a curative, a stabilizer, a cure catalyst, a burn rate catalyst and a bonding agent.

20

15

5